WM170E

INDUSTRIAL WALL MOUNT LCD DISPLAY

Panel Type	17.0” TFT Active Matrix Panel
Max. Resolution	1280x1024 SXGA@75Hz
Pixel Pitch	0.264 (H) x 0.264 (V)
Contrast Ratio	600:1
Brightness	1,200 cd/m2
Back Light	LED
Display Area	338 x 270 mm
Response Time	5ms (Typ.)
Display Colors	16.7 M
Viewing Angle	170 (H), 160 (V)
Signal Connector	RGB Analog 0.7V Peak to Peak
VGA Input Signal	15 Pin D-sub for VGA, RCA Video in, S-video
OSD Control	Power Switch, Menu, Select (+, -), Auto
Operation Temperature	0° ~ 50° C
Storage Temperature	-20° ~ 60° C
Power Consumption	40 W
Power Supply	External Power Adapter
Safely & EMI	CE, FCC, TUV-GS, UL Compliant
Front Bezel	Metal frame front cover
Mounting	Frame mount, VESA Mount (VESA 75/100)
LCD Protection	Option: Anti-Reflection Tempered Glass
Touch Screen	Option: Resistive/ Capacitive/ SAW; RS232/USB
Dimension	410 x 333.94 x 78 (mm) (not include OSD Keyboard) 16.14” x 13.15” x 3.07”
Net Weight	13 lbs (5.9 kg)

ACCUVIEW INC•
Tel: 800.275.4255 Fax: 201-440-5655 Address: 40C Cotters Lane, Suite F, East Brunswick Email: sales@accuview.com
*Specifications subject to change without notice. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 Accuview Inc. All rights reserved.